Cooperative Extension The University of Arizona College of Agriculture

## Landscape Safety Series: Tractor-Mower Safety<sup>1</sup>

Lance Fluegel and Bradley Rein<sup>2</sup>

## **BEFORE USING THE MOWER**

- Read or review the operator's manual to familiarize yourself with the machine.
- Learn the location and use of controls, gauges, and dials for the tractor.
- Familiarize yourself with speeds, slope capabilities, braking and steering characteristics, and tractormower clearances.
- Be sure the tractor is equipped with a roll-over protective structure (ROPS) and a seat belt. If not, have it retrofitted for one.
- Check that the power take off, mower input driveline, drive belts, chains, and gears are all properly guarded. Repair or replace if necessary.
- Check the discharge chute to see that it is present and pointed downward.
- Fill the fuel tank out of doors with the engine stopped and cool. Do not smoke while filling.
- If you will be driving on public roads be sure the slow moving vehicle (SMV) emblem is in place. Check that the warning lights are present and operating.
- Check overhead clearance of electrical wires and other obstructions, especially if you are using a wing-type, boom-type, or flail mower.

 Inspect the work area for debris, ditches, potholes, stumps, irrigation valves, etc. Clear removable items and mark the others.

## **OPERATING THE TRACTOR MOWER**

- Be sure your hands and shoes are clean and dry before mounting the tractor to prevent slipping. Use the steps and handbars.
- Do not allow any riders -- especially children.
- Adjust the seat, fasten the seat belt, set the parking brake, place shift lever in neutral or park, and disengage the pto before cranking the engine.
- Raise the mower high and use low rpm before engaging power to the unit.
- Use a ground speed based on length and density of material being cut -- normally between 2-5 mph.
- Mow very tall grass twice at 90-degree angles if possible.
- Mow up and down slopes with rear-mount, pull-type, and wing-type mowers.
- Mow across slopes with side-mount, offset, and sicklebar mowers.
- Look behind you before backing.

2. Lance Fluegel, Safety Coordinator, and Bradley Rein, Engineering Specialist, the College of Agriculture, University of Arizona, Tucson AZ 85719.

The University of Arizona College of Agriculture is an Equal Opportunity employer authorized to provide research, educational information and other services only to individuals and institutions that function without regard to sex, race, religion, color, national origin, age, Vietnam Era Veteran's status, or handicapping condition.

<sup>1.</sup> This document is 8831-K, a series of the the Cooperative Extension, the University of Arizona, Tucson, AZ 85719. Publication date: May 1989.

## OTHER DO'S AND DON'TS

- When finished or stopping, disengage the pto, place shift in neutral or park, set parking brake, turn engine off, and wait for all movement to stop before dismounting.
- Remove the key if leaving the tractor for any length of time.
- Always block the mower if working under it for any reason.